

MILITARY **LS-6090A/TA** LOUDSPEAKER



**NEW!**  
★ FOR TACTICAL FORCES ★

# LS-6090/TA

## MILITARY LOUDSPEAKER FOR TACTICAL FORCES

Military loudspeaker **LS-6090/TA** is a 6.5 inch direct radiator, dynamic, permanent magnet type loudspeaker housed in a die cast metal enclosure and is resistant to weather, water immersion, humidity, temperature extremes, vibrations and bounce. It is intended for use with ground, airborne and seaborne service. Tactical equipment is mobile or fixed field communications equipment.

### Characteristics :

**Frequency Range :**  
40 Hz-3000 Hz.

**Power Rating :**  
4 Watts RMS (nominal) and  
8 Watts RMS to peak.

**Input level :**  
The input level for the following requirements is 10 mV- 3 V RMS. AGC system presents.

**Impedance :**  
The input impedance of the **LS-6090A/TA** is between 1100 Ohms.

**Attenuation :**  
The **LS-6090A/TA** output is attenuated at no less than 40 dB when using the volume control.

**Temperature :**  
-30 to + 70 C

**Dimensions :**  
220 mm x 160 mm x 200 mm

**Net weight :**  
About 5 kg.

10 Hamelacha St. Block 209  
New Industrial park  
Rosh-Hayin 48091, Israel  
P.O.Box 13204 Tel-Aviv 61131  
Fax: 972 3 9025684  
Tel: 972 3 9025682  
E-mail: [peryphton@zahav.net.il](mailto:peryphton@zahav.net.il)  
[www.peryphton.co.il](http://www.peryphton.co.il)